

NX-3200/3300/3400

MULTI-PROTOCOL DIGITAL & ANALOG PORTABLE RADIOS

This versatile handheld radio supports both NXDN® and DMR digital protocols as well as mixed digital & FM analog operation, enabling it to serve with distinction in a wide range of enterprise and operation-critical applications. Compact yet designed with durability in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. Three different models with 14-pin Universal connector are available: Full Keypad model with LCD, Standard Keypad model with LCD and a large 4-way D-pad, and the Basic Model without LCD or keypad. Additionally, for expansion capability a software license certification system facilitates extensive customization.

Features

Multi-protocol digital radio: Designed to operate under NXDN® or DMR digital, and FM analog protocols

NXDN Conventional and Type-C & Gen2 Trunking

DMR Tier 2 Conventional & Site Roaming

DMR Auto Slot Select

DMR Tier 3 Trunking

Mixed Digital & FM Analog Operation allows gradual migration at your own pace

4-Line Basic Frame (2-Line Main/Sub-LCD, icon & key guide) / 14 Characters

5-Line Text Message Frame (3 Lines of Text, icon & key guide)

7-color Light Bar Indicator on the top panel. Individual color can be set for each channel

4-way Directional-pad (D-pad) for intuitive control and operation

Built-In GPS Receiver/Antenna for effective fleet and incident management

Built-in Bluetooth® for hands-free operation for IoT applications - Applicable Bluetooth profiles: HSP (Headset Profile) and SPP (Serial Port Profile)

Renowned KENWOOD Audio Quality achieved with Active Noise Reduction (ANR) that utilizes built-in DSP

Optional DES and AES Encryption

Built-in Motion Sensor (Man-down, Stationary and Motion Detection)

IP67 and MIL-STD-810 C/D/E/F/G

1 Watt Audio Output Power

Available models: Full Keypad (w/ LCD and full keypad), Standard Keypad (w/ LCD and 4-way large D-pad/4 key), and Basic (w/o LCD and keypad)

512 CH/128 Zones (64 CH/4 Zones for Basic model)

Maximum of 1,000 CH/Radio with option

CSA Intrinsically Safe Option:

Class I, II, III, Division 1, Groups A,B,C,D,E,F,G. Division 2 Groups A,B,C,D

Paging Call

Emergency Call

Status/Text Message

Remote Stun/Kill/Check

NXDN® DMR

Gen2

Bluetooth®

GPS FleetSync®

SP

DMR T3 S

DMR Auto Slot Select



Full Keypad, Standard & Basic Models

7-color Light Bar Indicator

14-pin Universal Connector offers reliable connectivity even in harsh environment with a wide-range of accessories.

Digital – NXDN® Mode

NXDN Conventional
NXDN Type-C & Gen2 Trunking
6.25 & 12.5 kHz Channels
Advanced GPS

Remote Monitor
All Group Call
Over-the-Air Alias (OAA)
Over-the-Air Programming (OTAP)

Digital – DMR Mode

Two-slot TDMA in 12.5 kHz channels
DMR Tier 2 Conventional / Site Roaming
DMR Auto Slot Select
DMR Tier 3 Trunking
Call Interruption

Dual-slot Direct Mode
Optional ARC4 Encryption
Energy Efficient
Over-the-Air Programming (OTAP)

Analog – FM Mode

Conventional & LTR Trunking
FleetSync/II: PTT ID ANI / Caller ID Display,
Selective Group Call, Emergency Status
Text Messages

MDC-1200: PTT ID ANI / Caller ID
Display, Emergency, Radio Check /Inhibit
QT / DQT, DTMF, 2-Tone
Built-in Voice Inversion Scrambler



Multi-Protocol

Unsurpassed interoperability for Enterprise radio users with the freedom to migrate at your own pace.



Gen2

Scalable server-based system architecture for management of NEXEDGE wide area digital communications systems.



Klarity

The ultimate level of sound clarity technology combining Optimization, advanced Sound Analysis and Active Noise Reduction.

Accessories

All accessories may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories.

KNB-55LA/57LA/78L

Li-ion Battery Pack (7.4V/1480mAh, 7.4V/2000mAh, 7.4V/2860mAh)



KNB-56N

Ni-MH Battery Pack (7.2 V/1400 mAh)



KNB-79LC

Li-ion Battery Pack (7.4 V/2860 mAh, Intrinsically Safe)



KBP-5

Battery Case (6 AA)



KSC-25LSK/25SK

Rapid Charger (Li-ion Only/Tri-Chem)



KSC-256AK

Multiple Charger (6-pocket)



KMB-30A

Mounting Bracket (for KSC-256AK)



KVC-23

Vehicular Charger



KRA-22/23

VHF/UHF Low Profile Helical Antenna



KRA-25

High Gain VHF Whip Antenna



KRA-26/ 27

VHF Helical Antenna UHF Whip Antenna



KRA-28

Broadband VHF Whip Antenna



KRA-29P

UHF Broadband Antenna (406-470MHz)



KRA-32K

700/800MHz Whip Antenna



KRA-36

700/800MHz Stubby Antenna



KRA-38K

800/900MHz Whip Antenna (included with NX-3400/NX-3420)



KRA-39

900MHz Stubby Antenna



KMC-70

IP68 Immersion, Compatible with ANR feature, NXDN/DMR Speaker Microphone with 3.5mm Ear jack & 3 Function Buttons




KMC-72W

IP67 Immersion, NXDN/DMR Speaker Microphone with 3.5mm Ear jack & 2 Function Buttons



KMC-70GR

Green, IP68 Immersion, Compatible with ANR feature, NXDN/DMR Speaker Microphone with 3.5mm Ear jack & 3 Function Buttons



KEP-1

Earphone Kit for KMC-70/70GR/72W



KBH-11

Belt Clip (2.5")



KAS-20

AVL & Dispatch Software

KPG-180AP

OTAP Manager

Specifications

General	NX-3200	NX-3300	NX-3400
Frequency Range	138-174 MHz	4061-470 MHz	TX/RX: 851-870, 935-941 MHz TX:806-825, 896-902 MHz
Max. Channels Per Radio		Up to 1000 CH with option	
Number of Channels		512 (64 for no LCD models)	
Number of Zones		128 (4 for no LCD models)	
Channel Spacing			
Analog	12.5/15/25/30 kHz	12.5/25 kHz	12.5/25 kHz
Digital	6.25 kHz/12.5 kHz	6.25 kHz/12.5 kHz	6.25 kHz/12.5 kHz
Power Supply		75V DC ± 20%	
Battery Life 5-5-90	(FDMA conventional / Trunking, TDMA Conventional / Trunking)		
KNB-55LA (1,480 mAh)	8.5 / 6.5 hours, 12.5 / 9 hours		9 / 7 hours, 12 / 9 hours
KNB-56N (1,400 mAh)	7.5 / 6 hours, 11 / 8 hours		8 / 6 hours, 10.5 / 8 hours
KNB-57LA (2,000 mAh)	12 / 9.5 hours, 17.5 / 13 hours		13 / 10 hours, 17 / 13 hours
KNB-78L (2,860 mAh)	17.5 / 13.5 hours, 25 / 18.5 hours		18.5 / 14 hours, 24 / 18.5 hours
KNB-79LC (2,860 mAh)	15 / 11.5 hours, 21.5 / 16 hours		15.5 / 12 hours, 20.5 / 16 hours
Operating Temperature		-22°F to +140°F (-30°C to +60°C)	
Frequency Stability		±0.5 ppm (-30°C to +60°C; +25°C Ref.)	
Dimensions		(W x H x D) Projections Not Included	
Radio Only		2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)	
KNB-55L (1,480 mAh)		2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)	
KNB-56N (1,400 mAh)		2.20 x 4.71 x 1.68 in (56 x 119.6 x 42.7 mm)	
KNB-57L (2,000 mAh)		2.20 x 4.71 x 1.53 in (56 x 119.6 x 39 mm)	
KNB-78L, KNB-79LC		2.20 x 4.71 x 1.77 in (56 x 119.6 x 44.9 mm)	
Weight Radio Only		7.8 oz (220 g)	
KNB-55L (1,480 mAh)		11.1 oz (315 g)	
KNB-56N (1,400 mAh)		14.5 oz (410 g)	
KNB-57L (2,000 mAh)		12.0 oz (340 g)	
KNB-78L, KNB-79LC		13.6 oz (385 g) / 13.9 oz (395 g)	
IC Certification	282F-479000	282F-479100	282F-502500

Battery Life is measured by Battery Save ON, GPS/Bluetooth OFF, 4 W for VHF/UHF and 3 W for 800/900MHz Bands. Specifications are subject change without notice, due to advancements in technology.

Receiver	NX-3200	NX-3300	NX-3400
Sensitivity			
NXDN* 6.25 kHz Digital (3% BER)		0.20 µV	
NXDN*12.5 kHz Digital (3% BER)		0.25 µV	
DMR 12.5 KHz Digital (5% BER)		0.30 µV	
DMR 12.5 KHz Digital (1% BER)		0.45 µV	
Analog (12dB SINAD)		0.25 µV	
Selectivity			
Analog @ 12.5kHz	65 dB		60 dB
Analog @ 25kHz	72 dB		70 dB
Intermodulation		70 dB	
Spurious Rejection		70 dB	
Audio Distortion		3%	
Audio Output Power	500 mW/8Ω (3% Distortion) / 1,000 mW/8Ω (5% Distortion)		

Transmitter	NX-3200	NX-3300	NX-3400
RF Power Output (High / Mid / Low)	5 W / 4 W / 1 W		3 W / 1 W
Spurious Emission	-70 dB		
FM Hum & Noise			
Analog @ 12.5kHz		40 dB	
Analog @ 25kHz		45 dB	
Audio Distortion	Less than 3%		
Digital Protocol	ETSI TS 102 361-1, -2, -3, -4		
Emission Designator	16K0F3E, 14K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXD, 7K60FXE, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D		

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. NXDN* is a registered trademark of JVC/KENWOOD Corporation and Icom Inc. NEXEDGE* & FleetSync* are a registered trademarks of JVC/KENWOOD Corporation. All other trademarks are the property of their respective holders.

MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	5001/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	5011/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	5021/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	5031/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	5051/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	5061/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	5071/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	5091/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	5101/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV

International Protection Standard

Dust & Water Protection	IP67 and MIL-STD-810 C/D/E/F/G
CSA Intrinsically Safe	Class I, II, III, Division 1, Groups A,B,C,D,E,F,G, Division 2 Groups A,B,C,D

JVC/KENWOOD Canada Inc.
Canadian Headquarters and Distribution
6685 Millcreek Drive, Unit 8, Mississauga, ON L5N 5M5
www.kenwood.com/ca



ISO9001 Registered
Communications Systems Business Unit
JVC/KENWOOD Corporation

ADS#13222