



Application Scenarios



Restaurant

cafe

Bookstore

Beauty Salon

• Standard • Optional

RO03

Specifications

General	
Model	S1-Mini
Frequency Range	400-440 MHz, 430-470 MHz
Analog/Digital	Analog
Channel Capacity	16
Zone Capacity	1
Operating Voltage	3.8V (Rated)
Battery	750mAh Li-Polymer (Built-in)
Battery Life (5/5/90 Duty Cycle, TX Power)	With earpiece: 16 hrs (1W)/18 hrs (0.5W)
Dimensions (HxWxD)	99*30*16mm (without belt clip)
Weight (With battery and antenna)	48 g
Display	0.88 inch
BT	BLE (only data) 5.0

Receiver	
Sensitivity	0.14µV
Rated Audio Power Output	0.5W

Transmitter	
Power Output	400-440 MHz, 430-470 MHz: 1W
Audio Response	+1 to -3dB
Audio Distortion	≤3%

Environment	
Operating Temperature	-10°C~ +55°C
Storage Temperature	-30°C ~ +70°C
ESD	±4kV (Contact) ±8kV (Air)

Hytera

Hytera Communications Canada

Address: Unit 11, 100 Leek Crescent, Richmond Hill, ON L4B 3E6 Tel: 905 305 7545 https://www.hytera.ca info@hytera.ca







Strap

16-pocket charger

Type-C Charging Cable



• Adapter



Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HTT, Hytera are registered trademarks of Hytera Communications Canada ©2024 Hytera Communications Canada. All Rights Reserved.

